

200mW SOD-323 Fast Switching Diode

Features

- 50nS; Fast Switching Device (TRR <50 nS)
- 200mW; Power Dissipation of 200mW
- High Stability and High Reliability
- Low reverse leakage



Marking :JR

Mechanical Data

- SOD-323 Small Outline Plastic Package
- Polarity: Color band denotes cathode end
- Mounting Position: Any

Maximum Ratings& Thermal Characteristics (T _A =25°C unless otherwise noted)					
Parameters	Symbol	Value	Unit		
Reverse Voltage	V_{R}	200	V		
Peak Reverse Voltage	V_{RRM}	200	V		
Power Dissipation	PD	200	mW		
Operating junction temperature	TJ	150	$^{\circ}$		
Storage temperature range	T _S	-55-+150	$^{\circ}$ C		
Thermal Resistance from Junction to Ambient	R _{θJA}	635	°C/W		
Average Rectified Current	I _O	200	mA		
Peak Forward Surge Cu rrent @tp=1us; TA=25 ℃	I _{FSM}	625	mA		

Valid provided that electrodes are kept at ambient temperature.

Electrical Characteristics (T _A =25°C unless otherwise noted)					
Parameter	0	Test Condition	Limits		Unit
	Symbols		Min	Max	Offic
Reverse Voltage	V(BR)	IR=100uA	250		V
Reverse Leakage Current	lR	VR=200V		1	uA
Forward Voltage V _F	VF	IF=100mA		1.00	V
		IF=200mA		1.25	·
Reverse Recovery Time	Trr	$ \begin{aligned} & \text{IF} = \text{IR} = 30\text{mA}, \\ & \text{Irr} = 0.1\text{XIR} \\ & \text{RL} = 100\Omega \end{aligned} $		50	nS
Capacitance	Cj	VR=0V, f=1MHZ		5.0	pF



Ratings and Characteristics Curves

(TA = 25°C unless otherwise noted)




Figure 2. Forward Current

Figure 3. Leakage Current






Figure 4. Total Capacitance






Package Outline Dimensions millimeters







Symbol	Min	Max
Α		1.000
A 1	0.000	0.100
A2	0.800	0.900
b	0.250	0.350
С	0.080	0.150
D	1.200	1.400
E	1.600	1.800
E1	2.500	2.700
L	0.475REF	
L1	0.250	0.400
θ	00	80

Revision History

Document Version	Date of release	Description of changes
Rev.A	2018.01.12	First issue





Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-Ark Electronics Co., Ltd.or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page. (http://www.goodark.com)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, Please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.