

1.5W,9.1 - 200V Zener Diodes

Features

- Low leakage current
- Available in unidirectional
- Glass passivated junction
- Zener voltage tolerance is $\pm 5\%$
- Total power dissipation: Max 1.5W
- Moisture sensitivity: level 1, per J-STD-020
- Halogen-free according to IEC 61249-2-21 definition



Applications

Protection from high voltage, high energy transients, voltage stabilization.

Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise noted)			
Parameter	Symbol	Ratings	Unit
Zener voltage	V_Z	See Next Table	V
Power dissipation at $T_L=75^\circ\text{C}$	P_{tot}	1.5	W
Maximum instantaneous forward voltage at 200mA	V_F	1.2	V
Typical Thermal Resistance , Junction to Ambient	$R_{\theta JA}$	85	$^\circ\text{C/W}$
Typical Thermal Resistance , Junction to Case	$R_{\theta JC}$	15	$^\circ\text{C/W}$
Typical Thermal Resistance , Junction to Lead	$R_{\theta JL}$	18	$^\circ\text{C/W}$
Operating junction and storage temperature range	T_J, T_{STG}	-55 to +150	$^\circ\text{C}$

Note:

1. The thermal resistance from junction to ambient, case or lead, mounted on P.C.B with 5×5mm copper pads



Electrical Characteristics (TA = 25 °C unless otherwise noted)

Part Number	Marking	V _Z at I _{ZT} (V)			I _{ZT} (mA)	Maximum zener impedance		I _{ZK} (mA)	Maximum reverse leakage at V _R (μA)	Test voltage V _R (V)	Maximum Zener Current I _{ZM} (mA)
		Min	Typ	Max		Z _{ZT} at I _{ZT} (Ω)	Z _{ZK} at I _{ZK} (Ω)				
L1N5924	5924	8.65	9.1	9.56	41.2	4	500	0.5	5	7.0	164
L1N5925	5925	9.50	10	10.50	37.5	4.5	500	0.25	5	8.0	150
L1N5926	5926	10.45	11	11.55	34.1	5.5	550	0.25	1	8.4	136
L1N5927	5927	11.40	12	12.60	31.2	6.5	550	0.25	1	9.1	125
L1N5928	5928	12.35	13	13.65	28.8	7	550	0.25	1	9.9	115
L1N5929	5929	14.25	15	15.75	25.0	9	600	0.25	1	11.4	100
L1N5930	5930	15.20	16	16.80	23.4	10	600	0.25	1	12.2	93
L1N5931	5931	17.10	18	18.90	20.8	12	650	0.25	1	13.7	83
L1N5932	5932	19.00	20	21.00	18.7	14	650	0.25	1	15.2	75
L1N5933	5933	20.90	22	23.10	17.0	17.5	650	0.25	1	16.7	68
L1N5934	5934	22.80	24	25.20	15.6	19	700	0.25	1	18.2	62
L1N5935	5935	25.65	27	28.35	13.9	23	700	0.25	1	20.6	55
L1N5936	5936	28.50	30	31.50	12.5	28	750	0.25	1	22.8	50
L1N5937	5937	31.35	33	34.65	11.4	33	800	0.25	1	25.1	45
L1N5938	5938	34.20	36	37.80	10.4	38	850	0.25	1	27.4	41
L1N5939	5939	37.05	39	40.95	9.6	45	900	0.25	1	29.7	38
L1N5940	5940	40.85	43	45.15	8.7	53	950	0.25	1	32.7	34
L1N5941	5941	44.65	47	49.35	8.0	67	1000	0.25	1	35.8	31
L1N5942	5942	48.45	51	53.55	7.3	70	1100	0.25	1	38.8	29
L1N5943	5943	53.20	56	58.80	6.7	86	1300	0.25	1	42.6	26
L1N5944	5944	58.90	62	65.10	6.0	100	1500	0.25	1	47.1	24
L1N5945	5945	64.60	68	71.40	5.5	120	1700	0.25	1	51.7	22
L1N5946	5946	71.25	75	78.75	5.0	140	2000	0.25	1	56.0	20
L1N5947	5947	77.90	82	86.10	4.6	160	2500	0.25	1	62.2	18
L1N5948	5948	86.45	91	95.55	4.1	200	3000	0.25	1	69.2	16
L1N5949	5949	95.0	100	105.0	3.7	250	3100	0.25	1	76.0	15
L1N5950	5950	104.5	110	115.5	3.4	300	4000	0.25	1	83.6	13
L1N5951	5951	114.0	120	126.0	3.1	380	4500	0.25	1	91.2	12
L1N5952	5952	123.5	130	136.5	2.9	450	5000	0.25	1	98.8	11
L1N5953	5953	142.5	150	157.5	2.5	600	6000	0.25	1	114.0	10
L1N5954	5954	152.0	160	168.0	2.3	700	6500	0.25	1	121.6	9
L1N5955	5955	171.0	180	189.0	2.1	900	7000	0.25	1	136.8	8
L1N5956	5956	190.0	200	210.0	1.9	1200	8000	0.25	1	152.0	7

Ratings and Characteristics Curves

($T_A = 25^\circ\text{C}$ unless otherwise noted)




Figure 1. Typical Zener Voltage




Figure 2. Steady State POWER Derating




Figure 3. Typical Instantaneous Forward Characteristics




Figure 4. Typical Zener Impedance







Figure 5. Typical Junction Capacitance

Package Outline Dimensions


in inches (millimeters)

eSGB (DO-221AC)



DIM	Unit: mm		Unit: inch	
	MIN	MAX	MIN	MAX
A	0.92	1.08	0.036	0.043
A1	0	0.1	0.000	0.004
B	1.25	1.45	0.049	0.057
C	0.1	0.25	0.004	0.010
D	2.6	2.8	0.102	0.110
E	4.1	4.3	0.161	0.169
L	0.7	1.1	0.028	0.043
HE	4.8	5.2	0.189	0.205

Soldering footprint



Revision History

Document Version	Date of release	Description of changes
Rev.A	2021.06.15	Released Datasheet
Rev.B	2023.10.12	Modify document format
Rev.C	2023.12.18	Update product range
Rev.D	2023.12.29	Modify package name

Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-Ark Electronics Co., Ltd. or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page.

(<http://www.goodark.com>)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, Please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.